

# **X-LINE MINI - LED every 25mm - 12W to 48W - up to 4968 lm - 340 mm to 1240 mm**

## **820-2125-HT X-LINE MINI 12 350mA warm white 3000K 2x22.5° L340mm 6W IP66**



### APPLICATION

High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.  
Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc ...

### LIGHTING FEATURES

CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

### ELECTRICAL FEATURES

Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

### CABLES USED

Fixed version: 2 x 0.5 mm<sup>2</sup> cable: black- and red+. Length: 150cm.  
Control version: 6 x 0.5 mm<sup>2</sup> cable: red channel (red+ and red/black-), green channel (green+ and green/black-), blue channel (blue+ and blue/black-). Length: 150cm.

### MECHANICAL FEATURES

IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified. Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total warm white 3000K (lm)	690
lm/W LED warm white 3000K	115
Qty LED	12
Ta max.	50°C
Tj (at 25°C)	85°C

### POWER

Product Led Power (W)	6
-----------------------	---