

## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0145-WL-HT X-LINE QUATTRO 5 230V WIRELESS DMX RGB-4000K 2x17° L360mm 19W IP66



## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0145-WL-HT X-LINE QUATTRO 5 230V WIRELESS DMX RGB-4000K 2x17° L360mm 19W IP66

### APPLICATION

High-power LED luminaire for outdoor lighting available in custom colours. DO NOT RECESS.  
Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...

### LIGHTING FEATURES

CRI70. 230V luminaire for outdoor lighting with 20 or 40 LED: : RGBW or customised choice of 2 to 4 colours.

### ELECTRICAL FEATURES

CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection.

### MECHANICAL FEATURES

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Weights: 360mm : 3,8 kg. 673mm : 7 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total neutral white 4000K (lm)	612,5
Lumen nominal total red (lm)	223
Lumen nominal total green (lm)	471
Lumen nominal total royal blue (mW)	2609,5
lm/W LED neutral white 4000K	118,9
lm/W LED red	60,3
lm/W LED green	88,9
mW/W LED royal blue	501,8
Qty LED	5
Ta max.	50°C
Tj (at 25°C)	85°C

### INRUSH CURRENT

Inrush Current (A)	60
--------------------	----

### POWER

Product Led Power (W)	19,4
Product Power (W)	24,8

