


# **POWERFLOOD 3 - Monochrome - 14W - 1896 lm**

829-0715 POWERFLOOD 3 24V CONTROL 3000K 2×17° Ø166mm 14W IP66



**POWERFLOOD 3 - Monochrome - 14W - 1896 lm**  
**829-0715 POWERFLOOD 3 24V CONTROL 3000K 2x17° Ø166mm 14W IP66**



**APPLICATION**

Monochrome LED projector for outdoor lighting.  
For use in urban lighting, squares, car parks, architectural accentuation etc...

**LIGHTING FEATURES**

CRI70. 3 LEDs. Monochrome.

**ELECTRICAL FEATURES**

Luminaires are wired in parallel using a separate 24V DC power supply + 10 kA/5 kA surge protector. Luminaire comes in a fixed or dimmable version. Control and cable length to be specified when ordering.

**CABLES USED**

Fixed version: HO5RN-F 2x1mm² cable: blue- & brown+.  
DMX version: numbered black cable, 3x1mm². 1 (V-), 2 (V+), 3 dimming.  
DALI version: 4x0,5mm² cable (red, green, blue & black).

**MECHANICAL FEATURES**

IP66, IK08. Cast aluminium, sandblasted RAL paint to be specified when ordering.  
Extra-white tempered glass. Captive stainless steel fasteners with Delta Seal®. Glare shield comes in raw aluminium with the RAL colour to be specified. Wind pressure = 0,04m². Weight: 2,3 kg.

**WARRANTY**

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

**LUMEN DATA**

|                                           |       |
|-------------------------------------------|-------|
| Lumen nominal total warm white 3000K (lm) | 1644  |
| lm/W LED warm white 3000K                 | 118,4 |
| Qty LED                                   | 3     |
| Ta max.                                   | 30°C  |
| Tj (at 25°C)                              | 85°C  |

**POWER**

|                       |      |
|-----------------------|------|
| Product Led Power (W) | 13,9 |
|-----------------------|------|