

## POWERFLOOD 9 – CUSTOM COLOURS - 35W

829-0305-WL POWERFLOOD 9 230V WIRELESS DMX RGBW 2x11° Ø257mm 37W IP66



## POWERFLOOD 9 – CUSTOM COLOURS - 35W

829-0305-WL POWERFLOOD 9 230V WIRELESS DMX RGBW 2x11° Ø257mm 37W IP66

### APPLICATION

LED projector for outdoor lighting.  
For use in urban lighting, squares, car parks, architectural accentuation etc...

### LIGHTING FEATURES

CRI70. 36 CUSTOM COLOUR LEDs

### ELECTRICAL FEATURES

230V mains connection. Integrated DMX driver in mounting base and DMX CONNECT SYSTEM plug and socket connectors. Built-in 10 kV/5 kA surge protection. Concealed cable to be specified when ordering.

### CABLES USED

Fixed version: HO7RN-F 3G1,5mm<sup>2</sup> cable: phase (brown), neutral (blue) & ground (green/yellow).  
DMX version on pole: {3G1,5mm<sup>2</sup> cable + 2x0,22mm<sup>2</sup> cable (blue, brown, green/yellow + white(data -) red (data +) + braid)} + 2x0,22mm<sup>2</sup> cable (white (data -) red (data +) + braid).  
DMX version on wall: CONNECT SYSTEM cable. Length: 50cm.

### MECHANICAL FEATURES

IP66, IK10. Cast aluminium, sandblasted RAL paint to be specified when ordering. Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®. Glare shield comes in raw aluminium with the RAL colour to be specified.  
Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®. Glare shield in raw aluminium, and RAL paint to be defined. Wind pressure = 0,1m<sup>2</sup>. Weight: 11 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total neutral white 4000K (lm)	688,5
Lumen nominal total red (lm)	371,7
Lumen nominal total green (lm)	789,3
Lumen nominal total blue (lm)	141,3
lm/W LED neutral white 4000K	75
lm/W LED red	55,1
lm/W LED green	82
lm/W LED blue	15,4
Qty LED	9
Ta max.	30°C
Tj (at 25°C)	85°C

### INRUSH CURRENT

Inrush Current (A)	55
Inrush Current Time (µs)	270

### POWER

Product Led Power (W)	34,7
Product Power (W)	43,8