

# POWERFLOOD 18 - Separate power supply box - 77W - 10750 lm

## 829-4230-HT POWERFLOOD 18 1,05A 2700K 2x11° Ø330mm 56W IP66



### APPLICATION

Monochrome LED projector for outdoor lighting.  
For use in urban lighting, squares, car parks, architectural accentuation etc...

### LIGHTING FEATURES

CRI70. 18 LEDs monochrome.

### ELECTRICAL FEATURES

Luminaires are wired in parallel using a separate power supply box with integrated 10 kV/5 kA surge protection for the pole. Control and cable length to be specified when ordering.

### CABLE USED

Fixed & controlled version: HO5RN-F 2x1mm² cable: blue- et brown+.

### MECHANICAL FEATURES

IP66, IK10. Cast aluminium, sandblasted RAL paint to be specified when ordering. Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®. Glare shield comes in raw aluminium with the RAL colour to be specified. Wind pressure = 0,15m². Weight: 13 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total warm white 2700K (lm)	6912
lm/W LED warm white 2700K	122,7
Qty LED	18
Ta max.	50°C
Tj (at 25°C)	85°C

### POWER

Product Led Power (W)	56,3
-----------------------	------