


X-LINE MINI - LED every 75mm - 4W to 16W - up to 1656 lm - 340 mm to 1240 mm
820-3405 X-LINE MINI 12 700mA royal blue 2x15° L940mm 12W IP66



APPLICATION
High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.
Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc...

LIGHTING FEATURES
CRI70. High-power LED luminaire. LED spacing 1 LED every 75 mm. Monochrome version.

ELECTRICAL FEATURES
Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Default cable length 1.5m.

CABLES USED
Fixed version: 2 x 0.5 mm² cable: black- and red+. Length: 150cm.
Control version: 6 x 0.5 mm² cable: red channel (red+ and red/black-), green channel (green+ and green/black-), blue channel (blue+ and blue/black-). Length: 150cm.

MECHANICAL FEATURES
IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified. Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

WARRANTY
5-year warranty: on LED module and driver (see the FLUX conditions).



Lifetime: 60 000 hours L80 B10

LUMEN DATA	
Lumen nominal total royal blue (mW)	5688
mW/W LED royal blue	469,3
Qty LED	12
Ta max.	30°C
Tj (at 25°C)	85°C
POWER	
Product Led Power (W)	12,1