

X-LINE QUATTRO - Custom colours - 29W to 58W

823-0105 X-LINE QUATTRO 5 230V DMX RGB-3000K 2x5° L360mm 29W IP66



X-LINE QUATTRO - Custom colours - 29W to 58W

823-0105 X-LINE QUATTRO 5 230V DMX RGB-3000K 2x5° L360mm 29W IP66

APPLICATION

High-power LED luminaire for outdoor lighting available in custom colours. DO NOT RECESS.
Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...

LIGHTING FEATURES

CRI70. 230V luminaire for outdoor lighting with 20 or 40 LED: : RGBW or customised choice of 2 to 4 colours.

ELECTRICAL FEATURES


CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection.

MECHANICAL FEATURES

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Weights: 360mm : 3,8 kg. 673mm : 7 kg.

WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



Lifetime: 60 000 hours L80 B10

LUMEN DATA

| | |
|---|-------|
| Lumen nominal total warm white 3000K (lm) | 722,5 |
| Lumen nominal total red (lm) | 314 |
| Lumen nominal total green (lm) | 595,5 |
| Lumen nominal total royal blue (mW) | 3557 |
| lm/W LED warm white 3000K | 95,7 |
| lm/W LED red | 56,6 |
| lm/W LED green | 75,9 |
| mW/W LED royal blue | 465 |
| Qty LED | 5 |
| Ta max. | 30°C |
| Tj (à 25°C) | 85°C |

INRUSH CURRENT

| | |
|--------------------|----|
| Inrush Current (A) | 60 |
|--------------------|----|

POWER

| | |
|---------------------------|------|
| Puissance Led Produit (W) | 28,6 |
| Puissance Produit (W) | 34,7 |

