

**X-LINE UP<sup>2</sup> – Frosted glass - 6W to 36W - up to 2178 lm - 350 mm to 950 mm**  
**822-3360 X-LINE UP<sup>2</sup> 36 230V CONTROL blanc froid 6500K dépoli L950mm 36W IP67**



Light fixture



Blockout



## X-LINE UP<sup>2</sup> – Frosted glass - 6W to 36W - up to 2178 lm - 350 mm to 950 mm

### 822-3360 X-LINE UP<sup>2</sup> 36 230V CONTROL blanc froid 6500K dépoli L950mm 36W IP67

#### APPLICATION

LED inground luminaire (not suitable for walls and roads) for outdoor lighting or architectural lighting.  
This product requires good drainage.  
Accentuation, wallwasher and marker light.



#### LIGHTING FEATURES

CRI70. High-power LED luminaire. Monochrome version, RGB MIX or WHITE MIX.



#### ELECTRICAL FEATURES

230V mains connection. Integrated driver. Built-in 10 kV/5 kA surge protection. Control to be specified when ordering. Default cable length 1.5m. DMX version contains the plug and socket CONNECT SYSTEM for easy installation.

#### CABLES USED

Version fixe : câble HO7RN-F 3G1,5mm<sup>2</sup> : phase (marron), neutre (bleu) et terre (vert/jaune). Longueur : 150cm.  
Version pilotable en DMX : câble CONNECT SYSTEM. Longueur : 50cm.  
Version pilotable en DALI : câble HO7RN-F 3G1,5mm<sup>2</sup> : phase (marron), neutre (bleu) et terre (vert/jaune) + câble 2x0,5mm<sup>2</sup> : noir- et rouge+. Longueur : 150cm.

#### MECHANICAL FEATURES

IP67, IK10. 304 stainless steel frame. Body in painted aluminium. Glass (thickness 19 mm) frosted. Supplied with blackout (thickness 5 mm) in Surtec 650 treated and painted aluminium. Weights: 350mm : 5,8 kg. 650mm : 10,3 kg. 950mm : 15 kg.

#### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).

**Lifetime: 60 000 hours L80 B10**

#### LUMEN DATA

Lumen nominal total cold white 6500K (lm)	2325,6
lm/W LED cold white 6500K	129,2
Qty LED	36
Ta max.	30°C
Tj (à 25°C)	85°C

#### INRUSH CURRENT

Inrush Current (A)	50
Temps Inrush Current (µs)	210

#### POWER

Puissance Led Produit (W)	18
---------------------------	----

