

# POWERFLOOD 9 - Separate power supply box - 39W - 5370 lm

829-0520 POWERFLOOD 9 1,4A 3000K 2x5° Ø257mm 38W IP66



## APPLICATION

Monochrome LED projector for outdoor lighting.  
For use in urban lighting, squares, car parks, architectural accentuation etc...

## LIGHTING FEATURES

CRI70. 9 LEDs monochrome.

## ELECTRICAL FEATURES

Luminaires are wired in parallel using a separate 24V DC power supply + 10 kV/5 kA surge protector for the pole. Luminaire comes in a fixed or dimmable version. Control and cable length to be specified when ordering.

## CABLE USED

Fixed & controlled version: HO5RN-F 2x1mm² cable: blue- et brown+.

## MECHANICAL FEATURES

IP66, IK10. Cast aluminium, sandblasted RAL paint.  
Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®.  
Glare shield in raw aluminium, and RAL paint to be defined. Wind pressure = 0,09m². Weight: 8 kg.

## WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

## LUMEN DATA

Lumen nominal total warm white 3000K (lm)	4653
lm/W LED warm white 3000K	120,5
Qty LED	9
Ta max.	30°C
Tj (at 25°C)	85°C

## POWER

Product Led Power (W)	38,6
-----------------------	------