

# POWERFLOOD 18 - Separate power supply box - 77W - 10750 lm

829-0660 POWERFLOOD 18 1,4A 6500K 2x3,7° Ø330mm 77W IP66



## APPLICATION

Monochrome LED projector for outdoor lighting.  
For use in urban lighting, squares, car parks, architectural accentuation etc...

## LIGHTING FEATURES

CRI70. 18 LEDs monochrome.

## ELECTRICAL FEATURES

Luminaires are wired in parallel using a separate power supply box with integrated 10 kV/5 kA surge protection for the pole. Control and cable length to be specified when ordering.

## CABLE USED

Fixed & controlled version: HO5RN-F 2x1mm² cable: blue- et brown+.

## MECHANICAL FEATURES

IP66, IK10. Cast aluminium, sandblasted RAL paint to be specified when ordering. Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®. Glare shield comes in raw aluminium with the RAL colour to be specified. Wind pressure = 0,15m². Weight: 13 kg.

## WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

## LUMEN DATA

Lumen nominal total cold white 6500K (lm)	11232
lm/W LED cold white 6500K	145,5
Qty LED	18
Ta max.	30°C
Tj (at 25°C)	85°C

## POWER

Product Led Power (W)	77,2
-----------------------	------

