

## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0575-WL-HT X-LINE QUATTRO 10 230V WIRELESS DMX WHITE MIX 2x17° L673mm 38W IP66



## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0575-WL-HT X-LINE QUATTRO 10 230V WIRELESS DMX WHITE MIX 2x17° L673mm 38W IP66

### APPLICATION

High-power LED luminaire for outdoor lighting available in custom colours. DO NOT RECESS.  
Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...

### LIGHTING FEATURES

CRI70. 230V luminaire for outdoor lighting with 20 or 40 LED: : RGBW or customised choice of 2 to 4 colours.

### ELECTRICAL FEATURES

CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection.

### MECHANICAL FEATURES

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Weights: 360mm : 3,8 kg. 673mm : 7 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

|  |       |
|--|-------|
| Lumen nominal total (lm)                     | 4600  |
| Lumen nominal total warm white 2700K (lm)    | 1075  |
| Lumen nominal total warm white 3000K (lm)    | 1075  |
| Lumen nominal total neutral white 4000K (lm) | 1225  |
| Lumen nominal total cold white 6500K (lm)    | 1225  |
| lm/W LED total                               | 111,6 |
| lm/W LED warm white 2700K                    | 104,4 |
| lm/W LED warm white 3000K                    | 104,4 |
| lm/W LED neutral white 4000K                 | 118,9 |
| lm/W LED cold white 6500K                    | 118,9 |
| Qty LED                                      | 10    |
| Ta max.                                      | 50°C  |
| Tj (at 25°C)                                 | 85°C  |

### INRUSH CURRENT

|                          |     |
|--------------------------|-----|
| Inrush Current (A)       | 70  |
| Inrush Current Time (µs) | 435 |

### POWER

|                       |      |
|-----------------------|------|
| Product Led Power (W) | 41,2 |
| Product Power (W)     | 51,2 |

