

# **POWERFLOOD 9 - Separate power supply box - 39W - 5370 lm** **829-0420-HT POWERFLOOD 9 1,05A 4000K 2x11° Ø257mm 28W IP66**



## **APPLICATION**

Monochrome LED projector for outdoor lighting.  
 For use in urban lighting, squares, car parks, architectural accentuation etc...

## **LIGHTING FEATURES**

CRI70. 9 LEDs monochrome.

## **ELECTRICAL FEATURES**

Luminaires are wired in parallel using a separate 24V DC power supply + 10 kV/5 kA surge protector for the pole. Luminaire comes in a fixed or dimmable version. Control and cable length to be specified when ordering.

## **CABLE USED**

Fixed & controlled version: HO5RN-F 2x1mm² cable: blue- et brown+.

## **MECHANICAL FEATURES**

IP66, IK10. Cast aluminium, sandblasted RAL paint.  
 Extra-white tempered glass. Silicone gasket. Captive stainless steel fasteners with Delta Seal®.  
 Glare shield in raw aluminium, and RAL paint to be defined. Wind pressure = 0,09m². Weight: 8 kg.

## **WARRANTY**

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

## **LUMEN DATA**

Lumen nominal total neutral white 4000K (lm)	4194
lm/W LED neutral white 4000K	148,9
Qty LED	9
Ta max.	50°C
Tj (at 25°C)	85°C

## **POWER**

Product Led Power (W)	28,2
-----------------------	------

