

**X-LINE UP<sup>2</sup> - Clear glass - 12W to 36W - up to 3726 lm - 350 mm to 950 mm**  
**822-3860 X-LINE UP<sup>2</sup> 36 230V CONTROL WHITE MIX 2×15° L950mm 36W IP67**



Light fixture



Blockout



# X-LINE UP<sup>2</sup> - Clear glass - 12W to 36W - up to 3726 lm - 350 mm to 950 mm

## 822-3860 X-LINE UP<sup>2</sup> 36 230V CONTROL WHITE MIX 2x15° L950mm 36W IP67

### APPLICATION

Inground luminaire (not suitable for walls and roads), adjustable LED for outdoor lighting or architectural lighting. This product requires good drainage.  
Accentuation, wallwasher and marker light.



### LIGHTING FEATURES

CRI70. High-power LED luminaire. Monochrome version, RGB MIX or WHITE MIX.



### ELECTRICAL FEATURES

230V mains connection. Integrated driver. Built-in 10 kV/5 kA surge protection. Control to be specified when ordering. Default cable length 1.5m. DMX version contains the plug and socket CONNECT SYSTEM for easy installation.

### CABLES USED

Version fixe : câble HO7RN-F 3G1,5mm<sup>2</sup> : phase (marron), neutre (bleu) et terre (vert/jaune). Longueur : 150cm.

Version pilotable en DMX : câble CONNECT SYSTEM. Longueur : 50cm.

Version pilotable en DALI : câble HO7RN-F 3G1,5mm<sup>2</sup> : phase (marron), neutre (bleu) et terre (vert/jaune) + câble 2x0,5mm<sup>2</sup> : noir- et rouge+. Longueur : 150cm.

### MECHANICAL FEATURES

IP67, IK10. 304 stainless steel frame. Body in painted aluminium. Glass (thickness 19 mm) clear. Adjustable clear glass version can be tilted +/- 15°. Supplied with blackout (thickness 5 mm) in Surtec 650 treated and painted aluminium. Weights: 350mm : 5,8 kg. 650mm : 10,3 kg. 950mm : 15 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).

**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total (lm)	3732
Lumen nominal total warm white 3000K (lm)	1164
Lumen nominal total neutral white 4000K (lm)	1242
Lumen nominal total cold white 6500K (lm)	1326
lm/W LED total	102,6
lm/W LED warm white 3000K	96
lm/W LED neutral white 4000K	102,5
lm/W LED cold white 6500K	109,4
Qty LED	36
Ta max.	30°C
Tj (at 25°C)	85°C

### INRUSH CURRENT

Inrush Current (A)	55
Inrush Current Time (µs)	270

### POWER

Product Led Power (W)	36,4
-----------------------	------

