

**X-LINE4 - DMX monochrome**

**810-5175-WL X-LINE4 36 230V WIRELESS DMX red 50x10° L937mm 27W IP66**



**APPLICATION**

230V AC (except for the USA) high-power LED luminaire for outdoor lighting available. DO NOT RECESS. Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...

**LIGHTING FEATURES**

CRI170. High-power LED luminaire. Monochrome DMX version.

**ELECTRICAL FEATURES**

CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection. For the USA please consult us.

**CABLES USED**

DMX version: CONNECT SYSTEM cable. Length: 50cm.

**MECHANICAL FEATURES**

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Weights: 337mm : 2 kg. 637mm : 3,5 kg. 937mm : 4,5 kg. 1237mm : 6,2 kg. 1537mm : 7,1 kg.

**WARRANTY**

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

**LUMEN DATA**

Lumen nominal total red (lm)	1688,4
lm/W LED red	64,2
Qty LED	36
Ta max.	30°C
Tj (at 25°C)	85°C

**INRUSH CURRENT**

Inrush Current (A)	55
Inrush Current Time (µs)	270

**POWER**

Product Led Power (W)	26,3
-----------------------	------

