

**X-LINE MINI - LED every 25mm - 12W to 48W - up to 4968 lm - 340 mm to 1240 mm**  
**820-4175 X-LINE MINI 48 700mA CONTROL royal blue 2x15° L1240mm 48W IP66**



**APPLICATION**  
High-power LED luminaire for architectural outdoor lighting. DO NOT RECESS.  
Backlight or accentuation light for use on cornices, rooves, diffused surfaces, walls, columns etc ...

**LIGHTING FEATURES**  
CRI70. High-power LED luminaire. LED spacing 1 LED every 25 mm. Monochrome version, RGB MIX or WHITE MIX.

**ELECTRICAL FEATURES**  
Luminaires are wired in series with a 700mA power supply + 10 kV/5 kA surge protector. Control is to be specified when ordering. Default cable length 1.5m.

**CABLES USED**  
Fixed version: 2 x 0.5 mm<sup>2</sup> cable: black- and red+. Length: 150cm.  
Control version: 6 x 0.5 mm<sup>2</sup> cable: red channel (red+ and red/black-), green channel (green+ and green/black-), blue channel (blue+ and blue/black-). Length: 150cm.

**MECHANICAL FEATURES**  
IP66, IK07. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Glare shield comes in raw aluminium with the RAL colour to be specified. Weights: 340mm: 0,75 kg. 640mm: 1,4 kg. 940mm: 2 kg. 1240mm: 2,5 kg.

**WARRANTY**  
5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

LUMEN DATA	
Lumen nominal total royal blue (mW)	22752
mW/W LED royal blue	469,3
Qty LED	48
Ta max.	30°C
Tj (at 25°C)	85°C
POWER	
Product Led Power (W)	48,5