

## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0010-WL X-LINE QUATTRO 5 230V DMX WIRELESS RGBW 2x11° L360mm 29W IP66



## X-LINE QUATTRO - Custom colours - 29W to 58W

823-0010-WL X-LINE QUATTRO 5 230V DMX WIRELESS RGBW 2x11° L360mm 29W IP66

### APPLICATION

High-power LED luminaire for outdoor lighting available in custom colours. DO NOT RECESS.  
Accentuation lighting for architectural facades, shop fronts, sculptures, columns etc...

### LIGHTING FEATURES

CRI70. 230V luminaire for outdoor lighting with 20 or 40 LED: : RGBW or customised choice of 2 to 4 colours.

### ELECTRICAL FEATURES


CONNECT SYSTEM for reliable and fast installation. Integrated DMX power supply. Built-in 10 kV/5 kA surge protection.

### MECHANICAL FEATURES

IP66, IK06. Anodized aluminium profile. Clear PMMA. Silicone gasket. Delta Seal® treated stainless steel fasteners. Weights: 360mm : 3,8 kg. 673mm : 7 kg.

### WARRANTY

5-year warranty: on LED module and driver (see the FLUX conditions).



**Lifetime: 60 000 hours L80 B10**

### LUMEN DATA

Lumen nominal total (lm)	1462,5
Lumen nominal total neutral white 4000K (lm)	514
Lumen nominal total red (lm)	290,5
Lumen nominal total green (lm)	553
Lumen nominal total blue (lm)	105
lm/W LED total	50,9
lm/W LED neutral white 4000K	68,5
lm/W LED red	51,9
lm/W LED green	69,1
lm/W LED blue	14
Qty LED	5
Ta max.	30°C
Tj (à 25°C)	85°C

### INRUSH CURRENT

Inrush Current (A)	60
--------------------	----

### POWER

Puissance Led Produit (W)	28,6
Puissance Produit (W)	34,7

